

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location System Location			
Address 7060 Oneka Lake 1	Blud	V	Telephone Number
City Huap StateMN ZIP 55038 Property ID No./GEO Code			
Owner Bill Urbaniak Pumping Date 10-18-16			
Contractor			
Maintainer R&M Septic MPCA License No. 7708 \(\sum 3070 \) Telephone Number (651) 674-8520			
What was done to the system?] [Repo	ort Liquid Capacity in Gallons
Tank(s) Pumped		Tank 1: 1500	Pumped Tank 2: Pumped
Sludge and scum measured.		Tank 3:	Pumped Tank 4: Pumped
Do tanks need to be pumped? Yes No (If no provide measurements below)		Total Gallons Pum	ped: 1500
	J L		
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.			
			a-
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped			
Tank Length in. X Tank Width in. X Tank Depth in. = Tank Volume (cubic inches)			
Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches)			
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch			
Sludge Level in. X Gallons Per Inch = Sludge Volume Gallons			
Scum Level in. X Gallons Per Inch = Scum Volume Gallons			
		***************************************	Gallons
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %			
Scum Layer Effluent Sludge Layer	from ir	Depth measured nvert of outlet o bottom of tank	*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity.
Signature Koray General	Date	10-18-	/6 Reset Form