

## DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

**GOVERNMENT CENTER** 

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## SSTS MAINTENANCE REPORT

System	Location
Address 23679 Meadow Drook Ave N. Telephone Number 651-433-453	
City Scandia State MN ZIP 55073 Property ID No./GEO Code	
Owner Tagno & Khaucy Pumping Date 10 ~ 21 - 16	
Contractor	
Maintainer R&M Septic MPCA License No. <del>7708</del> L 30 70 Telephone Number (651) 674-8520	
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped	Tank 1: / 000 Pumped Tank 2: 750 Pumped
Sludge and scum measured.	Tank 3: Pumped Tank 4: Pumped
Do tanks need to be pumped?  Yes No (If no provide measurements below)	Total Gallons Pumped: /750
Tes in the time provide medianements below)	
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.	
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. X Tank Width in. X Tank Depth in. = Tank Volume (cubic inches)	
Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches)	
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch	
Sludge Level in. <b>X</b> Gallons Per Inch = Sludge Volume Gallons	
Scum Level in. <b>X</b> Gallons Per Inch = Scum Volume Gallons	
Sludge Volume + Scum Volume = Total Sludge and Scum Volume Gallons	
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %	
	*Tanks must be pumped if either of the
The American Control of the Control	following conditions exist:  1. The top of the sludge layer is less than
Scum Layer	12 inches from the bottom of the outlet
	nk Depth measured baffle; or 2. Total sludge and scum volume is greater
pin	than 25 percent of the tank's liquid
Sludge Layer	capacity.
And admitted the above their subjects to the contract of the Manager and their subjects of	· ·
Signature Ryman Chung Date	10-20-16 Reset Form