

## DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## SSTS MAINTENANCE REPORT

	System Location
Address 8039-165 55 N	Telephone Number 426-9658
City Nuco	State ZIP 5058 Property ID No./GEO Code
Owner DENS SCALGTZ	Pumping Date //-//-
	Contractor
Maintainer Boss Pumping	MPCA License No. 1945 Telephone Number (651) 466-0800
What was done to the system?  Tank(s) Pumped Sludge and scum measured. Do tanks need to be pumped?  Yes No (If no provide measurements be	Tank 1: Pumped Tank 2: Pumped Tank 3: Pumped Tank 4: Pumped Total Gallons Pumped: / DO
Visual Inspection (note any problems with the	
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. <b>X</b> Tank Width	in. X Tank Depth in. = Tank Volume (cubic inches)
Tank Radius in. <b>X</b> Tank Radius in. <b>X</b> 3.14 = Tank Volume (cubic inches)	
Tank Volume (cu. in.) / 231.01 = Li	iquid Capacity Gallons / Tank Depth in. = Gallons/Inch
Sludge Level in. <b>X</b> Gallons Per Inch	= Sludge Volume Gallons
Scum Level in. <b>X</b> Gallons Per Inch	= Scum Volume Gallons
Sludge Volume + Scum Volume	= Total Sludge and Scum Volume Gallons
Total Sludge and Scum Volume / Lic	iquid Capacity = Percent Sludge and Scum in Tank %
Scum Layer  Effluent  Sludge Layer	*Tanks must be pumped if either of the following conditions exist:  1. The top of the sludge layer is less than  12 inches from the bottom of the outlet baffle; or  2. Total sludge and scum volume is greate than 25 percent of the tank's liquid capacity.
a. P.A.	Date // ) P// Reset Form