

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

movel broad milital his anagara of inchas				
		SystemiLocation		
Address 959	5 Jules 7	R	Telephone Number	
City Searce	lia	State ZIP	Property ID No./GEO Code	
Owner Ron	Bettner	Pumping Date /	2-1-15	
		conflactor -		
Maintainer 0/50	ns sewer	MPCA License No.	Telephone Number 651.	-464-2-82
What	vasidone forthe system?		ver Report Liquic Gapacity in Gallo	
Tank(s) Pumped		Tank 1	:1200 Pumped Tank 2: 152	Pumped
☐ Sludge and scun		Tank 3		Pumped
Do tanks need to			Gallons Pumped: 17	 -
L	o (If no provide measureme			
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.				
	*Tank Mea	stremens, Vasconiv, le cant. (Wara Not Rummers	
Tank Length	in. X Tank Width —	in. 🗶 Tank Depth	in. = Tank Volume (cubic inches)	
Tank Radius	in. 🗶 Tank Radius	in. X 3.14 = Tank	/olume (cubic inches)	
Tank Volume (cu. in.)	/ 231.01 =	Liquid Capacity	Gallons / Tank Depth in. = Gallor	ns/Inch
Sludge Level	in. X Gallons Per Inch	= Sludge Volume	Gallons	
Scum Level	in. X Gallons Per Inch	= Scum Volume	Gallons	
Sludge Volume	+ Scum Volume	= Total Sludge and Sc	rum Volume Gallons	
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %				
	_		*Tanks must be pumped if e	either of the
			following conditions exist:	
Scum Layer			1. The top of the sludge layer 12 inches from the bottom	
Effluent		Tank Depth me		
	The same of the sa	from invert of o	**************************************	
Sludge Layer		hihe to pottoll	capacity.	.
	in the last well in the second of			·
Signature ./	1/-	Date / ¬	1-16	