

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location		
Address 8265 - 805 50 W		Telephone Number
City CWAT	State ZIP P	roperty ID No./GEO Code
Owner ROGGL DUSUL	Pumping Date 4-74-17	A ALIA VA ANGERI A RESEARCE
	Contractor	and the second of the second o
Maintainer Boss Pumping	MPCA License No. 1945	Telephone Number (651) 466-0800
What was done to the system?		port Liquid Capacity in Gallons Pumped Tank 2: 400 Pumped
Tank(s) Pumped Sludge and scum measured.	Tank 3:	Pumped Tank 4: Pumped
Do tanks need to be pumped?	·	
Yes No (If no provide measurements be		mped: <u>COOO</u>
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.		
·		.iUN % & 2017
*Tank Measurements-Use Only If Tank (\$) Were NOT Pumped		
Tank Length in. X Tank Width		
Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches)		
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons / Inch		
Sludge Level in. X Gallons Per Inch	= Sludge Volume Gal	llons
Scum Level in. X Gallons Per Inch = Scum Volume Gallons		
Sludge Volume + Scum Volume = Total Sludge and Scum Volume Gallons		
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %		
		*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than
Scum Layer	<u></u>	12 inches from the bottom of the outlet baffle; or
Effluent Sludge Layer	Tank Depth measured from invert of outlet pipe to bottom of tank	2. Total sludge and scum volume is greater
January Co.		
Signature A	Date 4-74-/	7