

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT COVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT MONA Time

| Men sur |
|--|
| System Location |
| Address 23383 Melanie TVI N Telephone Number 651-433- |
| City Scandia State N ZIP 55073 Property ID No./GEO Code |
| Owner Richard Tetzlaff Pumping Date 6-6-16 |
| Contractor |
| Maintainer R&M Septic MPCA License No. 7708- 13 070 Telephone Number (651) 674-8520 |
| What was done to the system? Report Liquid Capacity in Gallons |
| ☐ Tank(s) Pumped ☐ Sludge and scum measured. Do tanks need to be pumped? ☐ Yes ☐ No (If no provide measurements below) Tank 1: |
| Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection |
| #246.00 |
| *Tank Measurements-Use Only If Tank(s) Were NOT Pumped |
| Tank Length in. X Tank Width in. = Tank Volume (cubic inches) |
| Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches) |
| Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons / Inch |
| Sludge Level in. X Gallons Per Inch = Sludge Volume Gallons |
| Scum Level in. X Gallons Per Inch = Scum Volume Gallons |
| Sludge Volume + Scum Volume = Total Sludge and Scum Volume Gallons |
| Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank % |
| *Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity. |
| Signature Augment Manage Date 6-6-16 Reset Form |