

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

3313 MAINTENANCE NET CITE			
	System Locatio	CONTRACTOR OF STREET	-4/ 1/01/
Address 8935 SCANDIA TI	L.N		Telephone Number 746 4916
city FONGS LOICE	State MN ZIP S	5025 Prope	erty ID No./GEO Code
Owner WAYNE NILES	Pumping Date 6	-20-17	9.50
Contractor			
Maintainer Boss Pumping	MPCA License No. 19		Telephone Number (651) 466-0800
What was done to the system? Tank(s) Pumped Sludge and scum measured. Do tanks need to be pumped? Yes No (If no provide measurements by the composition of the composition).	Tar pelow)	nk 1: /(XX) ** nk 3: al Gallons Pumpe	Pumped Tank 2: Pumped Pumped Tank 4: Pumped d: / SOO not serve as a compliance inspection.
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped			
Tank Length in. X Tank Width	in. 🗶 Tank Depth	in. =	Tank Volume (cubic inches)
Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches)			
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch			
	= Sludge Volume	e Gallon	s ·
Scum Level in. X Gallons Per Inch	= Scum Volume	Gallon	s
	= Total Sludge a	nd Scum Volume	Gallons
	iquid Capacity		ludge and Scum in Tank %
Total Sludge and Scum Volume/ L	iquid Capacity		and the second s
Scum Layer Scum Layer			*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet
Effluent Sludge Layer	from inv	oth measured ert of outlet oottom of tank	baffle; or 2. Total sludge and scum volume is greate than 25 percent of the tank's liquid capacity.
Signature Asia	Date	6-20-17	Reset Form