1 of 9

Inspect Minnesota & Midwest Soil Testing

P.O. Box 10853 White Bear Lake, MN 55110Brian Humpal651-492-7550/Brian@Midwestsoiltesting.comMPCA Licensed Advanced InspectorSUBSURFACE SEWAGE TREATMENT SYSTEM COMPLIANCE REPORT

Date:July 20, 2017Time:1:15 PMOwner:June Osborne

Inspection Address: 9040 60th St N, Grant, MN 55082

REPORT SUMMARY

I have performed an "MPCA Compliance Inspection" on this system. This very old system (installed in 1977) consists of a pre-cast septic tank and a rock trench drainfield.

My inspection indicates that this system is presently "non-compliant" in accordance with MPCA rules 7080.1500 Subp.4(B)(E) because of the lack of the required two foot separation between the bottom of the drainfield and seasonally saturated soils.

In accordance with MPCA rules, I am sending a copy of this complete report to Washington County. I cannot officially speak on behalf of the County relative to the upgrade requirements of these non-compliant systems. Please contact Washington County Environmental Specialist, Mr. Chris LeClair (651-430-4052), to verify the County's position.

Please advise buyer, agents, lender, etc. to contact me should they have any questions regarding this system.

Brian Humpal

Minnesota Pollution Control Agency	Со
520 Lafayette Road North St. Paul, MN 55155-4194	Exist

ompliance Inspection Form

ing Subsurface Sewage Treatment Systems (SSTS)

Doc Type: Compliance and Enforcement

nstructions: Inspection results based on Minnesota Pollution Control Agency (MPCA)
requirements and attached forms – additional local requirements may also apply.

Submit completed form to Local Unit of Government (LUG) and system owner within 15 days

System Status

System status on date (mm/dd/yyyy): 7/20/2017

Compliant – Certificate of Compliance

(Valid for 3 years from report date, unless shorter time frame outlined in Local Ordinance.)

🖄 Noncompliant – Notice of Noncompliance

For local tracking purposes:

(See Upgrade Requirements on page 3)

Reason(s) for noncompliance (check all applicable)

- □ Impact on Public Health (Compliance Component #1) Imminent threat to public health and safety
- Other Compliance Conditions (Compliance Component #3) Imminent threat to public health and safety

2 of 9

- Tank Integrity (Compliance Component #2) Failing to protect groundwater
- Other Compliance Conditions (Compliance Component #3) Failing to protect groundwater
- Soil Separation (Compliance Component #4) Failing to protect groundwater
- Operating permit/monitoring plan requirements (Compliance Component #5) Noncompliant

Property Information

Parcel ID# or Sec/Twp/Range: 34.030.21.33.0005

Property address: <u>9040 60th St N, Grant, MN 55082</u>	Reason for inspection: Property Transfer
Property owner: June Osborne	Owner's phone:
or	
Owner's representative: Lynn Clark	Representative phone: 612-964-4379
Local regulatory authority: Washington County	Regulatory authority phone: _651-430-4052
Brief system description: _ A pre-cast septic tank and a	rock trench drainfield.
Commonto or recommondationa:	

Comments or recommendations:

Certification

I hereby certify that all the necessary information has been gathered to determine the compliance status of this system. No determination of future system performance has been nor can be made due to unknown conditions during system construction, possible abuse of the system, inadequate maintenance, or future water usage.

Inspector name:	Brian Humpal	Certification number:	L5342
Business name:	Inspect Minnesota, Midwest Soil Testing	License number:	L2896
Inspector signatur	e: Brian Humpal	Phone number:	651-492-7550

Necessary or Locally Required Attachments

🛛 Soil boring logs	System/As-built drawing	Forms per local ordinance
Other information (list):	Report Summary, Property Information	tion, Disclaimer, License

1. Impact on Public Health – Compliance component #1 of 5

Compliance criteria:	
System discharge sewage to the ground surface.	🗌 Yes 🖾 No
System discharge sewage to drain tile or surface waters.	🗌 Yes 🖾 No
System cause sewage backup into dwelling or establishment.	🗌 Yes 🖾 No
Any "yes" answer above indicate	s the system is

Any "yes" answer above indicates the system is an Imminent Threat to Public Health and Safety.

Comments/Explanation:

None of the above found.

Verification method(s):

- Searched for surface outlet
- Searched for seeping in yard/backup in home
- Excessive ponding in soil system/D-boxes
- Homeowner testimony (See Comments/Explanation)
- "Black soil" above soil dispersal system
- System requires "emergency" pumping
- Performed dye test
- Unable to verify (See Comments/Explanation)
- Other methods not listed (See Comments/Explanation)

2. Tank Integrity – Compliance component #2 of 5

Compliance criteria:

System consists of a seepage pit, cesspool, drywell, or leaching pit.	🗌 Yes	🛛 No
Seepage pits meeting 7080.2550 may be compliant if allowed in local ordinance.		
Sewage tank(s) leak below their designed operating depth.	🗌 Yes	🛛 No
If yes, which sewage tank(s) leaks:		

Any "yes" answer above indicates the system is Failing to Protect Groundwater.

Comments/Explanation:

Lowered underwater camera into tank - baffles and tank walls OK.

Verification method(s):

Probed tank(s) bottom
Examined construction records
Examined Tank Integrity Form (Attach)
Observed liquid level below operating depth
Examined empty (pumped) tanks(s)
Probed outside tank(s) for "black soil"
Unable to verify (See Comments/Explanation)
Other methods not listed (See Comments/Explanation)

3. Other Compliance Conditions – Compliance component #3 of 5

a.	Maintenance hole covers are damage	d, cracked, ι	unsecured, or ap	opear to structurally	y unsound.	🗌 Yes*	🖾 No	🗌 Unknown

b. Other issues (*electrical hazards, etc.*) to immediately and adversely impact public health or safety. \Box Yes* \boxtimes No \Box Unknown *System is an imminent threat to public health and safety

Explain:

c. System is non-protective of ground water for other conditions as determined by inspector □ Yes* ⊠ No *System is failing to protect groundwater

Explain:

4. Soil Separation – Compliance component #4 of 5

Date of installation: _1977		own	Verification method(s):	
Shoreland/Wellhead protection/Food Beverage Lodging?	🗌 Yes	🛛 No	Soil observation does not expire. Pre	
Compliance criteria:			observations by two independent pa unless site conditions have been alte	
For systems built prior to April 1, 1996, and not located in Shoreland or Wellhead Protection Area or not serving a food, beverage or lodging establishment: Drainfield has at least a two-foot vertical separation distance from periodically saturated soil or bedrock.	☐ Yes	🖾 No	requirements differ. Conducted soil observation(s) (A Two previous verifications (Attack Not applicable (Holding tank(s), not Unable to verify (See Comments/Explanation) Other (See Comments/Explanation)	h boring logs) drainfield) Explanation)
Non-performance systems built April 1, 1996, or later or for non-performance systems located in Shoreland or Wellhead Protection Areas or serving a food, beverage, or lodging establishment:	☐ Yes	□ No	Comments/Explanation:	
Drainfield has a three-foot vertical separation distance from periodically saturated soil or bedrock.*				
"Experimental", "Other", or "Performance"	🗌 Yes	🗌 No	Indicate depths of elevations	
systems built under pre-2008 Rules; Type IV or V systems built under 2008 Rules (7080. 2350 or 7080.2400 (Advanced Inspector License required)			A. Bottom of distribution media	See Attached Boring Log(s)
Drainfield meets the designed vertical			B. Periodically saturated soil/bedrock	
separation distance from periodically saturated soil or bedrock.			C. System separation	
			D. Required compliance separation*	
Any "no" answer above indicates t Failing to Protect Groundwater.	he syste	em is	*May be reduced up to 15 percent if Ordinance.	allowed by Local
Operating Permit and Nitrogen B	MP* – Co	ompliance		icable
Is the system operated under an Operating Per	mit?	🗌 Yes [⊠ No If "yes", A below is required	
Is the system required to employ a Nitrogen BM	1P?	🗌 Yes 🛛	No If "yes", B below is required	
BMP=Best Management Practice(s) specif	ied in the s	system des	ign	
If the answer to both questions is "no",	this sect	tion does	not need to be completed.	
Compliance criteria				

	Operating Permit number: Have the Operating Permit requirements been met?	🗌 Yes 🗌 No
b.	Is the required nitrogen BMP in place and properly functioning?	🗌 Yes 🗌 No

Any "no" answer indicates Noncompliance.

5.

Upgrade Requirements (*Minn. Stat.* § 115.55) *An imminent threat to public health and safety (ITPHS) must be upgraded, replaced, or its use discontinued within ten months of receipt of this notice or within a shorter period if required by local ordinance. If the system is failing to protect ground water, the system must be upgraded, replaced, or its use discontinued within the time required by local ordinance. If an existing system is not failing as defined in law, and has at least two feet of design soil separation, then the system need not be upgraded, replaced, or its use discontinued, notwithstanding any local ordinance that is more strict. This provision does not apply to systems in shoreland areas, Wellhead Protection Areas, or those used in connection with food, beverage, and lodging establishments as defined in law.*

<u>Inspect Minnesota & Midwest Soil Testing</u>

Subsurface Sewage Treatment System Owner/Property Information

This information will be used for the purpose of conducting an MPCA Compliance Inspection.

Date of Inspection: July 20, 2017	Time: 1:15 PM					
Property Address: 9040 60 th St N, Grant, MN	Zip: 55082					
Property Owner: June Osborne	Phone:					
Tank(s)Tank(s)MaterialSoil TreatrSeptic 1FiberglassRock troAerobicPlasticGravello	nent System Other ench Alternative system ess trench Experimental system er trench Cesspool system e bed Other system					
Are the tank maintenance covers accessible? Performed through the maintenance holes. Maintenant the ground surface to facilitate access and proper main	ce hole covers should be made accessible to					
	977 Tank size (gals.): 1200					
	umber of residents in home?					
	lrained by gravity? Y					
	rlpool bath?					
More than one system (laundry, etc.)?						
Does this property have any footing drain tiles connec						
Are any buildings on this property such as garages or	out-oundings connected to this system?					
Are there any additional systems on this property serv	ing other buildings?					
Location of septic system on lot? Northwest Side						
Location of water well on lot? Southeast Side	Is the well a deep well? Y					
Have you ever experienced any problems with the system such as: tree roots, sewage back-ups, surfacing of sewage onto the ground, septic tank overflowing, etc.; or have any repairs been made to the system? If yes, explain:						
When was the system last pumped?	ame of pumper:					
How often pumped in previous years?	Is system on a monitoring plan?					
Have you received notices from any government agen						
Is your property located in a shoreland management area? N						
Do you have any additional information that should be given to the new owner?						

I hereby certify that the above information is correct to the best of my knowledge. I also understand that if the system is considered "non-compliant/failing" per MPCA rules, that the inspector must by law submit a copy of this report to the local government unit within 15 days of the date of inspection completion. I also agree that unless otherwise noted in this report, that I/we are ultimately responsible for payment of all fees for all work performed relative to this inspection by Inspect Minnesota and Midwest Soil Testing.

Owner/Occupant:

○ B-1 By Inspect MN Drainfield Area Septic Tank House $\text{Well} \bigcirc$ 9040 60th St N, Grant, MN 55082 NO SCALE

Log Of Soil Borings

Location of Project: 9040 60th St N, Grant, MN 55082						
		Inspect Minnesota		Date:	7/20/17	
		Hand/Bucket	Classif	Classification System: USDA		
E	Boring Number:	1		Boring Number:		
Surface Elevation o Boring	Same grou	und surface as last nfield trench	Surface Elevation c Boring			
Depth In Inches	<u>Soils E</u>	ncountered	Depth In Inches	Soils Er	ncountered	
0-6 6-16 16-27 27-46 46-64	10YR 3/3 9 10YF 7.5YR 4/4 L Trace 7.5YR 4/4 9 Trace O	/2 Silt Loam Silt Loam (Moist) A4/4 Loam Loamy Sand With e Of Gravel Sandy Loam With f Gravel With '8, & Few 10YR 6/2 Redox				
46" [Depth To End Of B	oring Or Redox	Depth To End Of Boring Or Redox			
Same E	Elevation Of Borin	g Relative To System	Elevation Of Boring Relative To System			
	Depth To Bottom (Of Separation	Of Distribution Media		Depth To Bottom C Df Separation	f Distribution Media	
E	End Of Boring At:	64"		End Of Boring At:		
	Redox Present At:			Redox Present At:		
Standing \	Water Present At:	None	Standing \	Water Present At:		

Bottom Of Distribution Medium At: 38 Inches

Brian L. Humpal, Inc. dba. Inspect Minnesota, Midwest Soil Testing

Relative to Subsurface Sewage Treatment System (SSTS) Compliance Inspections

- 1. This inspection/report is being performed for only the seller/owner of the property on which the SSTS is located. In such case that another party is paying for the inspection, the contract is between only said party and Brian L. Humpal, Inc.; there is no contract between Brian L. Humpal, Inc. and any other party unless otherwise noted.
- 3. Brian L. Humpal, Inc. has not been retained to warranty, guarantee, or certify the proper functioning of the SSTS for any period of time beyond the date of inspection or into the future. Because of the numerous factors (usage, maintenance, soil characteristics, previous failures, etc.) which may affect the proper operation of an SSTS, as well as the inability of Brian L. Humpal, Inc. to supervise or monitor the use or maintenance of the SSTS, the report shall not be construed as a warranty by Brian L. Humpal, Inc. that the SSTS will function properly for any particular party for any period of time.
- 4. Brian L. Humpal, Inc. is unable to verify the frequency and/or, quality of prior or future maintenance of the SSTS. Maintenance of the tank(s) must be performed through the tanks maintenance hole. The removal of solids from any location other than the maintenance hole is not a compliant method of maintenance. It is strongly recommended that maintenance covers be made accessible to the ground surface to facilitate proper maintenance.
- 5. Minimum Compliance Inspection requirements relative to this inspection and this report include <u>only</u> verification that the SSTS has tank(s) (septic tanks, lift tanks, dosing tanks, stilling tanks, etc.) which are watertight below the designed operating depth, the required separation between the bottom of the subsurface soil distribution medium and seasonally saturated soils, no back-ups of sewage into the dwelling, no discharge of sewage/effluent to the ground surface or surface waters, and no imminent safety hazards. Brian L. Humpal, Inc. does not inspect plumbing or pumps prior to the first SSTS component as these are plumbing components. The performance of exterior pumps and associated components are not inspected as they are considered to be maintenance items. Additionally, no indications relative to compliance with electrical code requirements have been made. It is recommended that any other applicable plumbing, electrical, housing, etc. inspections be performed by a qualified inspection business. Sewage back-up verification is limited to observing the floor drain area and/or the information supplied by the last occupants of the building prior to inspection. Brian L. Humpal, Inc. cannot guarantee that the information given to them by the last occupants of the building prior to inspection relative to back-ups is accurate.
- 4. Certification of this SSTS does not warranty future use beyond the date of the inspection. Any SSTS, old or new, can become hydraulically overloaded or discharge sewage/effluent to the ground surface as a result of more people moving into the house than were previously occupying the house, improper maintenance, heavy usage, leaking plumbing fixtures, groundwater infiltration, tree roots, freezing conditions, surface drainage problems, poor initial design, poor construction practices, or unsuitable materials used in constructing the system; the system can also simply stop working because of its age. An SSTS that has been properly designed and installed, properly maintained, and used in the manner for which the system was designed can be expected to provide service for twenty to twenty-five years on average. Some parts of the SSTS such as alarms, switches, pumps, filters, etc. will most likely have to be repaired or replaced over the lifetime of the system.
- 5. A Compliance Inspection is not meant to be a test or inspection for longevity of the system; a Compliance Inspection is strictly for the purpose of determining if the SSTS is protective of public health and safety, as well as the groundwater at the date and time the inspection was performed. This inspection is not intended to determine if the SSTS was originally designed or installed to past or present MPCA or other Local Government Unit code requirements. This inspection is not intended to determine if the SSTS was designed and/or installed to support the anticipated flow from the building as the use of the building may have changed since the design and construction of the SSTS due to the addition of bedrooms, occupants, etc. In addition, this inspection is not intended to determine the quality of the original SSTS design, the quality of the construction practices used while installing the SSTS, or the quality of the materials used in constructing the SSTS.
- 6. Brian L. Humpal, Inc. cannot guarantee the performance of SSTS products/components such as: gravelless pipe, chamber trenches, effluent filters, tanks, sewage pre-treatment components, piping, etc. Products such as gravelless pipe are no longer approved for installation in the State of Minnesota and may have a significantly reduced performance and/or life expectancy.
- 7. WINTER WORK: By accepting this report, it is understood that inspections conducted during winter months (approximately November 1st through April 1st) are more difficult to perform because of possible snow cover and/or ground frost. SSTS components such as tanks, maintenance covers, tank inspection pipes, subsurface distribution medium inspection pipes, and soil treatment areas are more difficult or impossible to locate due to snow cover and/or ground frost. In addition, soil borings are more difficult to perform due to snow cover and/or ground frost. Brian L. Humpal, Inc. will attempt to use the same level of standards when performing work during winter periods as when performing work during non-winter periods. However, the recipient of this report understands that because of the aforementioned considerations, the same level of standards may not be possible.
- 8. By accepting this report, the client understands that Brian L. Humpal, Inc. will not be responsible for any monetary damages exceeding the fee for the services provided.

Subsurface Sewage Treatment Systems Non-transferable Business License

Inspect Minnesota, Midwest Soil Testing

License # L2896

License Expires: 12/22/2017

Issued: 11/29/2016

Specialty Area(s): Installer Maintainer Service Provider Advanced Designer Advanced Inspector

Designated Certified Individual(s):

Cert #	Name	Certification Expires:
C5342	Brian L Humpal	10/15/2017
C9852	Installer, Maintainer, Serv Prov, Christopher R Uebe	3/4/2018
C9052	Designer, Inspector	5/4/2016



Minnesota Pollution Control Agency

520 Lafayette Road North St. Paul, Minnesota 55155-4194

Steven Giddings, Manager Prevention and Solid Waste Management Section